



ALL MECHANIC

Bomaksan Retrowall filter units are all mechanical plug&play units which does not need electrical or compressed air connection.

FILTER LEVEL DISPLAY

Mechanical differential pressure level indicator shows the filter clog level.

CLEANABLE CARTRIDGE FILTERS

Cartridge filters in the RETROWall is cleanable. They can be re-used after cleaned by compressed air.

GENERAL INFORMATION

Filter Type	Cartridge
Filter Media	
Standard	nanoBLEND FR
Optional	polyMIGHT PTFE 65
No of Cartridge Filters	1
Total Filtration Area	
Standard	18 m ²
Optional	12 m ²
Filtration Efficiency	
Standard	F9 Class
Optional	H13/H14 Class

ORDER NO

No Arm, SFS	RTW.0.18.B135FR
No Arm, OFS	RTW.0.12.265PTFE

SFS : Standard Filter Set

OFS: Optional Filter Set

TECHNICAL INFORMATION

Filtration Capacity	1.500 m ³ /h
Dimensions (W x L x H)	560 x 555 x 650 mm
Weight	35 kg
Motor Power	No Motor
Power Supply	No Need

*retroWALL series need to be equipped with an extraction fan, fan control panel and extraction hood (such as arm, bench, special designed hood, hose etc.)

SPARE PART ORDER NO

nanoBLEND FR Filter	HTM/380/400/B135FR/18
polyMIGHT PTFE 65 Filter	HTM/380/400/265PTFE/12